SOFT FLAG FABRIC
SP-110FR

GENERAL DESCRIPTION:

Super soft, - Good soft texture and double penetration effect, , etc.

FEATURES:

· Texturized Warp knit fabric that is 100% Polyester

· Compatible with Dye-sub direct, Dye-sub transfer, also workable with UV& Latex inks

· Excellent durability and tear strength

APPLICATIONS:

Mainly used for Flag &Banner applications.

MATERIAL DETAILS:

PROPERTIES	METRIC	TEST STANDARD	IMPERIAL
Finished Material Weight	110G/sq.m	DIN EN ISO 2286-2	3.24oz/sq m
Material	100%Polyester	DIN 60001	100%Polyester
Width	Up to 320cm	ASTM D751-2006	Up to 162"
Standard Length	50±10M / 100±10M	N/M	N/M
Weave Method	Warp-Knitted 3 bar	N/A	Warp-Knitted 3 bar
Thread Density	13w 18c	ASTM D-3887, Section 12	/
Shrinkage	≤ 2.5% (215℃, 1 min)	ISO 9866.2	
Surface	Matte		
Flame Retardance	Germany DIN 4102 - B1 /U.S.A NFPA-701	N/A	/
Yellowing temperature	210℃	SUPRKC REX-C400	

Dye Direct	Dye Transfer	Silk-Screen
√	√	√
Latex	UV	...
√	√	x

COMPATIBLE PRINTER:

Dye Direct	Dye Transfer	UV
Roland	Mutoh	HP
Mimaki	Mimaki	
Epson	Epson	
Dgen	Dgen	
Mutoh	Mutoh	

PRODUCTION DETAILS:

PACKAGE:	1. 3"plastic bags, individual packing with woven bags
	2. 3"plastic bags, individual packing, hard tubes with nail/ screw
WIDTH:	100-320CM
LENGTH:	Standard Length: 50±10M / 100±10M
	Others: each roll will has one tolerance length difference ±10%
DELIVERY TIME:	After received deposit 15~25 days
SHIPPING CONDITIONS:	FOB SHANGHAI
STORAGE:	Make-to-order after 3 orders will keep stable storage

NOTE: All mentioned data above are average of test result and should not be used for the purpose of lawsuit or warranty. This information should only be used as a guide and buyers shall independently test and determine products suitability.